

Budget Perimeter Benches – Cloakroom Seating Manufactured by:



Eastern Storage Equipment Ltd, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE
Telephone: 01603 629956 – Fax: 01603 630113 – Email: sales@versabench.co.uk
Website: www.cloakroomseating.co.uk



N10 - Specification:

'BBL...' - Budget Basic bench Complete:

Dimensions: 325mm deep x 450mm seat height

Standard sizes: 1m (2 sets legs) - 1.5m (3 sets legs) - 2m (3 sets legs)
2.5m (4 sets legs) - 3m (4 sets legs)

Leg frames: BBL - Constructed of 30mm x 30mm box section with floor fixing cleats (floor fixings not included), 300mm deep with 70mm wide top plate pre drilled (6 holes) ready to take 3 seat slats, ground and polished then powder coated to finish.

Seat slats: Ash heartwood - Consists of 3x 75mm x 25mm hardwood seat slats sanded and lacquered with sufficient screws supplied to fix slats to the legs.

FINISH:

Colours: Stocked in Silver (Chrome Silver Gloss) and also available in 5 additional colours - Blue (RAL5002) - Yellow (RAL1018) - Red (RAL3020) - Green (RAL6009) - Black (RAL9005).

Ash hardwood slats: Sourced via FSC (Forestry Stewardship Council) approved agents who only harvest timber from responsibly managed and sustainable forests. Members of TTF (Timber Trades Federation) with systems in place to ensure only legal timber handled. Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

Steel legs and seat support frames: Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

Pre Zinc coating: If the bench seats are for use in wet situations or where there is exposure to chlorine / bromine etc, please ensure you request Pre Zinc Coating (additional cost applicable).

Note: For high humidity, regularly wet areas, external or pool side applications we would recommend our Stainless Steel range.