

Club Range Benches – Cloakroom Seating Manufactured by:



Eastern Storage Equipment Ltd, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE
Telephone: 01603 629956 – Fax: 01603 630113 – Email: sales@versabench.co.uk
Website: www.cloakroomseating.co.uk



N10 - Specification:

'R45...' - Round Frame Deep Bench:

Dimensions: 450mm deep x 450mm high seat as standard (Junior – Infant sizes available).
1m - 1.5m - 2m long or 2.5m - 3m long with a third upright in the centre.
Designed to the Sport England and Football Foundation size guidelines.

Leg frames: Constructed of 45mm dia vertical tubes backset by 25mm from the front and rear of the seat to reduce risk of stubbing toes, with 50mm x 30mm horizontal channels, ground / polished then powder coated to finish, pre-drilled to take seat frames, and shoe rack (if required), with plastic feet as standard. Available as options - Floor fixing cleats - Adjustable feet.

Seat: Constructed using a powder coated 30x30 formed angle support framework for additional strength, onto which 4x 75mm x 25mm Ash hardwood slats are factory fitted.

OPTION:



Shoe Racks: Constructed using 3 powder coated round tubes and formed channel ends, simply bolts into the legs under the bench seat units at 150mm centres from the floor.

FINISH:

Colours: Available in a choice of 6 standard colours - Silver (Chrome Silver Gloss) - Blue (RAL5002) - Yellow (RAL1018) - Red (RAL3020) - Green (RAL6009) - Black (RAL9005).

Ash hardwood slats: Sourced via FSC (Forestry Stewardship Council) approved agents who only harvest timber from responsibly managed and sustainable forests. Members of TTF (Timber Trades Federation) with systems in place to ensure only legal timber handled. Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

Steel / metal legs and seat support frames: Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

Zinc Plating: If the bench seats are for use in wet situations or where there is exposure to chlorine / bromine etc, please ensure you request Zinc Plating (additional cost applicable).

Note: For high humidity, regularly very wet areas, external or pool side applications we would recommend our Stainless Steel range.