

Club Range Benches – Cloakroom Seating Manufactured by:



Eastern Storage Equipment Ltd, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE
Telephone: 01603 629956 – Fax: 01603 630113 – Email: sales@versabench.co.uk
Website: www.cloakroomseating.co.uk



N10 - Specification:

'RS...X' - Single Sided bench with Coat Hooks:

Dimensions: 400mm deep x 1750mm high, seat 450mm high standard (Junior – Infant sizes available). 1m - 1.5m - 2m long or 2.5m - 3m long with a third upright in the centre.

Leg frames: Constructed of 45mm dia vertical tubes with 50mm x 30mm horizontal channels, ground / polished then powder coated to finish and pre-drilled to take seat frames, and shoe rack (if required) with plastic feet as standard. Available as options - Floor fixing cleats - Adjustable feet.

Seat: Constructed using a powder coated 30x30 formed angle support framework for additional strength, onto which 3x 75mm x 25mm Ash hardwood slats are factory fitted.

Hat and Coat rail: Constructed of 75mm x 25mm Ash hardwood to one side of which Satin Anodised Aluminium two prong coat hooks are fitted.

1m = 5 hooks - 1.5m = 7 hooks - 2m = 10 hooks - 2.5m = 12 hooks - 3m = 14 hooks

OPTIONS:



Shoe Racks: Constructed using 3 powder coated 19mm round tubes and formed channel ends, simply bolts into the legs under the bench seat units at 150mm centres from the floor.

Back Rests: Constructed of 75mm x 25mm Ash hardwood rounded on all four edges and bolted to factory fitted steel mounting brackets on the uprights.

FINISH:

Colours: Available in a choice of 6 standard colours - Silver (Chrome Silver Gloss) - Blue (RAL5002) - Yellow (RAL1018) - Red (RAL3020) - Green (RAL6009) - Black (RAL9005).

Ash hardwood slats: Sourced via FSC (Forestry Stewardship Council) approved agents who only harvest timber from responsibly managed and sustainable forests. Members of TTF (Timber Trades Federation) with systems in place to ensure only legal timber handled. Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

Steel / metal legs and seat support frames: Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

Zinc Plating: If the bench seats are for use in wet situations or where there is exposure to chlorine / bromine etc, please ensure you request Zinc Plating (additional cost applicable).

Note: For high humidity, regularly very wet areas, external or pool side applications we would recommend our Stainless Steel range.