

Budget Perimeter Benches – Cloakroom Seating Manufactured by:



Eastern Storage Equipment Ltd, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE
Telephone: 01603 629956 – Fax: 01603 630113 – Email: sales@versabench.co.uk
Website: www.cloakroomseating.co.uk

N10 - Specification:

'BBL...' Budget Basic bench components:

Dimensions: 315mm deep x 450mm seat height as standard.



Leg frames: **BBL** - Constructed of 30mm x 30mm box section with floor fixing cleats (floor fixings not included), 300mm deep with 70mm wide top plate pre drilled (6 holes) to take 3 seat slats, ground and polished then powder coated to finish.



Seat slats: **AHT** or **ASH** - Consists of 3x 70mm x 25mm Ash hardwood slats sanded and lacquered with sufficient screws supplied to fix slats to the legs (legs ordered separately from seat slats).
1m - 1.5m - 2m - 2.5m - 3m long as standard.

FINISH:

Colours: Available in a choice of 6 standard colours - Silver (EW002E) - Blue (RAL5002) - Yellow (RAL1018) - Red (RAL3020) - Green (RAL6009) - Black (RAL9005).

Ash hardwood slats: Sourced via FSC (Forestry Stewardship Council) approved agents who only harvest timber from responsibly managed and sustainable forests. Members of TTF (Timber Trades Federation) with systems in place to ensure only legal timber handled. Ash is cut to size, profiled with an 8-10mm round on top 2 long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

Steel / metal legs and seat support frames: Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electrostatically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

Electro Zinc Plating: If the bench seats are for use in humid / wet situations or where there is risk of exposure to chemicals like chlorine / bromine etc, please ensure you request Electro Zinc Plating (additional cost applicable), and we will apply the plating after degreasing and before the final polyester powder coated colour finish is applied, OR Stainless Steel which will have a natural unpainted finish.